

## BPC 10 INSTALLATION

1. Make sure:
  - Application Server ABAP ? PI\_BASIS 7.3
  - I Application Server ABAP ? SAP ABA 7.3
  - I Application Server ABAP ? SAP BASIS 7.3
  - I Application Server ABAP ? SAP BW 7.3
  - I Kernel (64-bit) and Unicode only
2. Install Add-in POASBC ABAP component ? version POA\_SBC\_100\_730
  - Download those files
    - K-10101INPOASBC.SAR
    - K-10102INPOASBC.SAR
    - K-10103INPOASBC.SAR
    - K-10104INPOASBC.SAR
    - K-10105INPOASBC.SAR
    - K-10106INPOASBC.SAR
    - K-101AGINPOASBC.SAR
3. Install bpc10 + sp
4. Post installation
  - Run transaction RSTPRFC to set the BW client and name of the destination.
  - sm59 Test MDX PARSER
  - change abap/buffersize to 2000000 (for report UJS\_ACTIVATE\_CONTENT)
  - se06 ,open all
  - Assign the authorization SAP\_BW\_CONTENT\_ADMIN to the user installing
  - create a user BPC\_SERVICE with user type System Assign the role SAP\_BPC\_SERVICE to this user
  - sso
    - login/accept\_sso2\_ticket = 1.
    - login/create\_sso2\_ticket = 2 (recommended) or 1.
    - icm/host\_name\_full
    - snc/gssapi\_lib
    - ssf/ssfapi\_lib
    - sec/libsapsecu
    - ssl/ssl\_lib
  - HTTPS
    - make sure that you have SAP Cryptographic Library installed ([http://help.sap.com/saphelp\\_nw73/helpdata/en/49/236897bf5a1902e10000000a42189c/frameset.htm](http://help.sap.com/saphelp_nw73/helpdata/en/49/236897bf5a1902e10000000a42189c/frameset.htm))
    - Setting the Profile Parameters for Using SSL (example)
    - ssl/ssl\_lib = E:\usr\sap\B73\DVEBMGS00\exe\sapcrypto.dll
    - sec/libsapsecu = E:\usr\sap\B73\DVEBMGS00\exe\sapcrypto.dll
    - ssf/ssfapi\_lib = E:\usr\sap\B73\DVEBMGS00\exe\sapcrypto.dll
    - ssf/name = SAPSECULIB
    - icm/server\_port\_2 = PROT=HTTPS, PORT=443, TIMEOUT=900

- icm/HTTPS/verify\_client = 1
- (if you need redirect to java system use this parameter  
icm/http/j2ee\_<xx>)
- create PSE of SSL server standart
- RESTART the instance
- Install EnvironmentShell
  - logon to client 400 and make sure that scc4 is not set to "No changes allowed"
  - Run the program UJS\_ACTIVATE\_CONTENT
  - In the Content Activation window, set the Environment ID to EnvironmentShell and the Content Version to 1.
    - Choose the following options:
      - Update Language
      - Activate BI Business Content
      - Update Default DM Instructions
      - Activate EnvironmentShell
      - Update Default Formulas Table
    - Execute in background
    - Check the logs
    - There can be an X\_MESSAGE exception when running UJS\_ACTIVATE\_CONTENT to activate the environment EnvironmentShell.
    - For details of how to resolve this issue, see SAP Note 1576929.
- return abap/buffersize to original size
- restart the server
- ICF Services
  - Verify that the services activated under: SICF
    - /sap/EPM\_BPC
    - /poa
    - /sap/public/bc
    - /sap/bw/xml/soap/xmla/ (EPM connector)
- install notes:
  - 1673094
- Client
  - <http://www.adobe.com/go/getflash/>